

CODECO

LATENCY AND BANDWIDTH CONSIDERATIONS IN EDGE- CLOUD

Funded by
the European Union

INTRODUCTION TO LATENCY AND BANDWIDTH CONSIDERATIONS IN EDGE-CLOUD FOR IOT APPLICATIONS

The **Edge-Cloud** computing paradigm merges edge and cloud computing, allowing for data processing at the network's edge.

This architecture significantly reduces **latency** and optimises **bandwidth usage**, making it ideal for IoT applications. This presentation will explore the importance of latency, factors affecting it, strategies to reduce it, and considerations for bandwidth in Edge-Cloud setups.

IMPORTANCE OF LATENCY IN EDGE-CLOUD

Latency refers to the delay in data packet transmission between devices. In IoT applications, maintaining low latency is essential for **real-time data processing** and timely responses.

The Edge-Cloud architecture minimises latency by enabling data processing at the edge devices, significantly reducing the **round-trip time** to central cloud servers and facilitating faster decision-making based on analysed data.



Funded by the European Union

FACTORS AFFECTING LATENCY IN EDGE-CLOUD

Several factors influence latency in an Edge-Cloud setup:

- **Network Latency**: The time required for data packets to traverse the network infrastructure.
- **Data Processing Latency**: The duration taken for edge devices to process incoming data.
- **Communication Latency**: The delay involved when edge devices communicate with the cloud server.
- **Wireless Transmission Latency**: The latency introduced by wireless communication technologies.

Funded by the European Union

STRATEGIES TO REDUCE LATENCY IN EDGE-CLOUD

To minimise latency in Edge-Cloud setups, consider these strategies:

- **Edge Data Processing**: By processing data at the edge, round-trips to the central cloud server are reduced.
- **Caching**: Storing frequently accessed data at edge devices can significantly cut down latency by avoiding repeated requests to the cloud.
- **Predictive Analytics**: Implementing predictive analytics at edge devices allows for real-time data analysis and quicker decision-making.
- **Edge-Cloud Synchronisation**: Efficient synchronisation between edge devices and the cloud server helps minimise delays caused by data transfers.

BANDWIDTH CONSIDERATIONS IN EDGE-CLOUD

Bandwidth represents the maximum data transmission capacity over a network within a specified timeframe. In IoT applications, bandwidth limitations can create significant challenges, particularly with numerous devices generating large data volumes. The Edge-Cloud architecture effectively addresses these bandwidth concerns.

Funded by the European Union

STRATEGIES TO OPTIMISE BANDWIDTH USAGE IN EDGE-CLOUD

To optimise bandwidth utilisation in an Edge-Cloud setup, employ the following strategies:

- **Data Aggregation**: Combine data from multiple edge devices before sending it to the cloud server to reduce bandwidth usage.
- **Data Compression**: Compressing data before transmission decreases overall data size, optimising bandwidth.
- **Selective Data Transmission**: Only transmit relevant data from edge devices to the cloud server to minimise unnecessary bandwidth consumption.
- **Context-Awareness**: Assess the context of the IoT application and transmit only essential data for decision-making, conserving bandwidth resources.

CONCLUSION AND RECOMMENDATIONS

Latency and bandwidth considerations are vital for deploying IoT applications within an Edge-Cloud architecture. By minimising latency and optimising bandwidth, Edge-Cloud setups enhance **real-time data processing**, reduce response times, and improve overall efficiency. Understanding the factors affecting latency and employing strategies for reduction, alongside optimising bandwidth usage, allows developers to leverage the full potential of Edge-Cloud for IoT applications. Tailoring these strategies to meet specific IoT application requirements will ensure optimal performance in an Edge-Cloud environment.